RAP310-B650

AMD® Ryzen™ 7000 Series
microATX



Top View

KEY FEATURES

DDR5

4 DDR5 UDIMM up to 128GB

4K High Resolution

Supports 4K resolution

Triple Displays

1 VGA, 1 DP++, 1 HDMI

Multiple Expansion

2 PCIe x16, 2 PCIe x4,
1 M.2 E key, 1 M.2 M key,
4 SATA 3.0

Rich I/O

2 Intel 2.5GbE, 4 COM,
6 USB 3.2 Gen 2,
2 USB 3.2 Gen 1,
6 USB 2.0

BLOCK DIAGRAM



MECHANICAL DRAWING



SPECIFICATION

SYSTEM	**Processor**	AMD Ryzen 9 PRO 7945 AMD Ryzen 7 PRO 7745 AMD Ryzen 5 PRO 7645
	Chipset	AMD B650
	Memory	Four 288-pin UDIMM up to 128GB (Non-ECC) Dual Channel DDR5 5200 MHz ***Speed support list follow User's Manual**
	BIOS	AMI SPI 256Mbit
GRAPHICS	**Controller**	Navi2 Graphics
	Feature	1WGP @2.2GHz max
	Display	1 x VGA 1 x DP++ 1 x HDMI 2.0 **VGA:** resolution up to 1920x1200 @ 60Hz **DP++:** resolution up to 3840x2160 @ 60Hz **HDMI:** resolution up to 4096x2160 @ 60Hz
	Triple Displays	1 VGA + 1 DP++ + 1 HDMI 2.0
EXPANSION	**Interface**	2 x PCIe x16 (Gen 4, x16 or x8+x8) -Support PCIE1/PCIE3 : single at x16(PCIE1) -Support PCIE1/PCIE3 : dual at x8(PCIE1)/x8(PCIE3) -Support PCIE1 : Riser card x16 or x8/x8 selected by Jumper 2 x PCIe x4 (Gen 4) 1 x M.2 2230 E key 1 x M.2 2242/2260/2280 M key
AUDIO	**Audio Codec**	Realtek ALC888
ETHERNET	**Controller**	2 x Intel® I226V
REAR I/O	**Ethernet**	2 x 2.5GbE (RJ-45)
	Serial	1 x RS232
	USB	6 x USB 3.2 Gen 2 2 x USB 2.0
	Display	1 x VGA 1 x DP++ 1 x HDMI
	Audio	1 x Line-out 1 x Mic-in 1 x Line-in (opt. by request, MOQ required)
INTERNAL I/O	**Serial**	1 x RS-232/422/485 2 x RS232
	USB	2 x USB 3.2 Gen1 4 x USB 2.0 (colay vertical Type A)
	Audio	1 x Front Audio Header 1 x S/PDIF
	SATA	4 x SATA 3.0 RAID 0/1/5/10
	DIO	1 x 8-bit DIO
	PS/2	1 x PS/2
	SMBus/ I^2C	1 x SMBus/ I^2C
WATCHDOG TIMER	**Output & Interval**	System Reset, Programmable via Software from 1 to 255 Seconds
SECURITY	**TPM**	Nuvoton TPM 2.0
POWER	**Type**	ATX
	Connector	8-pin ATX 12V power
		24-pin ATX power
	Consumption	**Typical:** Ryzen 9 PRO 7945: 3.3V @ 0.14A (0.462W); 5V @ 0.96A (4.8W); 12V @ 0.66A (7.92W) **Max.:** Ryzen 9 PRO 7945: 3.3V @ 1.14A (3.762W); 5V @ 3.4A (17W); 12V @ 8.94A (107.28W)
	RTC Battery	CR2032 Coin Cell
OS SUPPORT	**Microsoft**	Windows 11 Enterprise Windows 10
	Linux	Ubuntu 22.04
ENVIRONMENT	**Temperature**	**Operating:** -5 to 65°C **Storage:** -40 to 85°C
	Humidity	**Operating:** 5 to 95% RH **Storage:** 5 to 95% RH
	MTBF	481,630 hrs @ 25°C; 277,744 hrs @ 45°C; 177,053 hrs @ 60°C; 130,262 hrs @ 70°C Calculation Model: Telcordia Issue 4 Environment: GB, GC - Ground Benign, Controlled
MECHANISM	**Dimensions**	microATX Form Factor 244mm (9.6") x 244mm (9.6")
	Height	**PCB:** 1.6mm **Top Side:** 38mm **Bottom Side:** 3mm
STANDARDS AND CERTIFICATIONS	**Certifications**	CE, FCC Class B, RoHS, UKCA

ORDERING INFORMATION

Model Name	P/N	Memory	2.5 GbE	COM	USB 3.2 Gen2	USB 3.2 Gen1	USB 2.0	TPM 2.0	Power	Temp.
RAP310-B650	770-RAP3101-000G	4 DDR5 UDIMM	2	4	6	2	4	dTPM	24-pin ATX/ 8-pin ATX 12V	-5 to 65°C

PACKING LIST

1 RAP310-B650 motherboard	
1 COM port cable (Length: 300mm, 2 x COM ports)	A81-015026-023G
1 Serial ATA data cable (Length: 500mm)	332-553001-005G
1 I/O shield	A49-RAP310-000G

OPTIONAL ITEMS

USB 2.0 port cable (Length: 350/398mm)	A81-001066-016G
USB 3.2 Gen2 port cable (Length: 350mm)	A81-001075-017G
COM port cable (Length: 300mm, 2 x COM ports)	A81-015026-023G
Serial ATA data cable (Length: 500mm, W/LOCK)	332-553001-005G
Serial ATA data cable (Length: 500mm, W/LOCK, 90D)	A81-002128-017G
Thermal solution (Cooler)	A71-101159-001G
DP to HDMI Dongle	612-D2H13M-000G
M.2-COM4 (M.2 serial port module)	770-M2COM1-000G
M.2-2LAN (M.2 LAN port module)	770-M22LN1-000G
M.2-2PSE (M.2 PSE module)	770-M22PS1-000G

DFI reserves the right to change the specifications at any time prior to the product's release. Changes thereafter will be based on the product's revision. Please contact your sales representative for the exact revision offered in your area. All product names mentioned are trademarks of their respective companies. © November 24, 2025 DFI Inc.