







**Bottom View** 



**Top View** 

## **KEY FEATURES**











## Qualcomm

Qualcomm<sup>®</sup> QCS8550 high-level platform

### LPDDR5

LPDDR5 on board memory up to 8GB

### Al Box

Target on edge AI box, AIoT application

# Ruggedized

Thin client concept and ruggedized design

## **Al Architecture**

Optimized AI architecture (48 INT8, 12 FP16 TOPs)

# **SPECIFICATION**

SYSTEM	Processor	Qualcomm <sup>®</sup> QCS8550 Kryo™ CPU, 8 cores, up to 3.2 GHz		
	Memory	8GB LPDDR5		
GRAPHICS	Controller	Qualcomm® Adreno™ 740 GPU		
	Feature	OpenGL ES 3.2		
	Display	1 x Micro HDMI		
STORAGE	UFS	128GB UFS 3.1		
EXPENSION	Interface	1 x M.2 B key 3052 (USB 3.1, PCle x1), reference module source: TBD		
		1 x Nano SIM slot		
AUDIO	Audio Codec	Audio codec WCD9385		
REAR I/O	USB	2 x USB 3.1 Gen1 Type A		
	Display	1 x Micro HDMI		
	Debug	1 x USB Type C (Download only)		
INTERNAL I/O	Audio	1 x Line out/Mic in		
	RF Connector	2 x RF connector (Integrated Wi-Fi 7)		
	Other I/O	1 x Power LED, 1 x System LED, 1 x Front Panel		
	Camera	1 x MIPI-CSI2 for 4-lanes camera, reference camera source: BMD13B (Sensor: IMX688)		
POWER	Туре	12VDC		
	Connector	2 pin Power Jack		
	Consumption	TBD		
OS SUPPORT	Linux	Android T/13, Kernel 5.15		
ENVIRONMENT	Temperature	Operating: -5°C~65°C	Storage: -40°C~85°C	
	Humidity	Operating: 5%~90% RH	Storage: 5%~90% RH	
MECHANISM	Dimensions	1.8" Pico-ITX Form Factor	84mm (3.31") x 68mm (2.67")	
	Height	PCB: 1.6 mm		
		Top Side: 13.8 mm		
		Bottom Side: 4.0 mm		
STANDARDS AND CERTIFICATIONS	Certifications	CE, FCC, RoHS, UKCA		

# **PACKING LIST**

• 1 AIMF51 board