# FC CE ROHS



**Front View** 



**Bottom View** 

## **KEY FEATURES**



DDR4

2GB/4GB/8GB DDR4 Memory Down



4K High Resolution

Supports 4K / 2K resolution



**Dual Displays** 

1 eDP/LVDS + 1 DP/TMDS



Multiple Expansion


2 PCle 3.0, 1 PCle 2.0



RICH I/O

1 Realtek GbE, 1 USB 3.0, 4 USB 2.0

# **MECHANICAL DRAWING**



Qseven Module Top Side

#### **SPECIFICATION**

SYSTEM	Processor	Rockchip RK3568 quad-core Cortex-A55 @2.0GHz						
	Manager	Rockchip RK3568J quad-core Cortex-A55 @1.8GHz 2GB/4GB/8GB DDR4 Memory Down 3200MHZ						
OD A DUUGO	Memory							
GRAPHICS	Controller	G52 2EE						
	Feature	OpenGL ES1.1/2.0/3.0/3.1/3.2, Vulkan 1.1, OpenCL 2.0						
	Display	1 x eDP/LVDS 1 x DP/TMDS	HDMI: resolution up to 4096 x 2160 @30HZ LVDS: resolution up to1024 x 600 @60Hz eDP: resolution up to 3840 x 2160 @60Hz					
	Dual Displays	eDP/LVDS + DP/TMDS						
EXPANSION	Interface	2 x PCIe x1 (Gen 3) 1 x PCIe x1 (Gen 2) 1 x uSD (available upon request) 1 x I2C 2 x SPI (SPI0 set to TPM 2.0) 1 x CAN bus 2 x UART 1 x MIPI-CSI (available upon request)						
AUDIO	Interface	HD Audio						
ETHERNET	Controller	1 x RTL8211F-CG						
1/0	USB	1 x USB 3.0 4 x USB 2.0						
	SATA	2 x SATA 3.0 (up to 6Gb/s, SATA 1 Co-Lay PCIE Gen 2)						
	eMMC	Supports up to 128GB eMMC, NC as default eMMC 5.1, BGA-153 Ball 8~128G(MLC mode)						
	GPI0	1 x 4-bit GPIO						
SECURITY	TPM	TPM 2.0						
POWER	Туре	5V, 5VSB, VCC_RTC						
	Consumption	TBD						
OS SUPPORT (UEFI ONLY)	Linux	Linux						
ENVIRONMENT	Temperature	Operating: 0 to 60°C, -40 to 85°C						
	Humidity	Operating: 5 to 90% RH Storage: 5 to 90% RH						
	MTBF	TBD						
MECHANICAL	Dimensions	Qseven form factor 70mm (2.76") x 70mm (2.76")						
	Compliance	Qseven specification revision 2.1						
STANDARDS AND CERTIFICATIONS	Certification	CE, FCC Class B, RoHS						

### **ORDERING INFORMATION**

Model Name	P/N	CPU	Memory	eDP	USB 3.0	USB 2.0	еММС	Operating Temp.
RK701-BC41-RK3568	770-RK7011-000G	RK3568	4 GB	LVDS	1	4	16GB	0 to 60°C
RK701-BC81-RK3568	770-RK7011-100G	RK3568	8 GB	LVDS	1	4	16GB	0 to 60°C
RK701-TC81-RK3568J	770-RK7011-200G	RK3568J	8 GB	LVDS	1	4	16GB	-40 to 85°C

#### **PACKING LIST**

#### • 1 RK700 board • 1 Heat sink

# **OPTIONAL ITEMS**

Qseven Carrier Board